



**PHYSICAL PROPERTIES & PACKAGING (FLOATING RESILIENT CLIC FLOORING)**

Product	<b>Allure Ultra Wide 8.7" x 47.6" Plank</b>
Size	8.7" x 47.6" (220mm x 1210mm)
Construction	Solid Vinyl Tile/LVT
Use	Commercial & Residential
Finish	Urethane with Ceramic Bead Particles
Wear Layer	20mil (0.5mm)
Edge Detail	Bevel Edge
Embossing(s)	In-Register
Gauge	0.197" (5.0mm)
Pieces/Carton	7
Coverage/Piece	2.866 Sq.Ft. (0.266 Sq.M.)
Coverage/Carton	20.06 Sq.Ft. (1.86 Sq.M.)
Limited Warranty	10-Year Commercial / Lifetime Residential

**NORTH AMERICAN STANDARDS – MANUFACTURING & USAGE (ASTM F1700)**

Standard	Description	Requirements	Results
ASTM F1700	Classification	Refer to Standard	Class III, Type B
ASTM F386	Thickness	±0.005"	Passes Requirements
ASTM F410	Wear Layer Thickness	Commercial Classification: ≥ 20mil (0.5mm)	Passes Requirements
ASTM F1914	Residual Indentation	Average <8%; Maximum - Any Sample ≤10%	Surpasses Requirements
ASTM F2199	Dimensional Stability	≤0.020"/Linear Foot	Surpasses Requirements
ASTM F925	Chemical Resistance	No more than "Slight Change"	Passes Requirements
ASTM F1514	Resistance to Heat	Average & Max ΔE < 8.0	Surpasses Requirements
ASTM F1515	Resistance to Light	Average & Max ΔE < 8.0	Surpasses Requirements

**NORTH AMERICAN STANDARDS – SAFETY & PERFORMANCE**

Standard	Description	Requirements	Results
ASTM E648	Radiant Panel (Critical Radiant Flux)	Class I: ≥ 0.45 W/cm <sup>2</sup>	Passes Requirements
ASTM E662	Smoke Density	Flaming & Non-Flaming ≤ 450	Passes Requirements
ASTM F963	Heavy Metals	Refer to Standard	Passes Requirements
ASTM D7823	Phthalates	Refer to Standard	Meets CPSIA Guidelines
ASTM D2047	Coefficient of Friction / Slip Resistance	N/A	≥0.6 (Dry)
ASTM F970	Static Load	±0.005", 250-Lbs. Load	Passes Requirements
SIM Test	Static Load Limit	Test to Limit	≥1,000 lbs.

**NORTH AMERICAN CERTIFICATIONS**

Standard	Description
FloorScore® CHPS 01350	This product is FloorScore® Certified (SCS-FS-02874) and has thus been found to comply with the volatile organic compound emissions criteria of the California Section 01350 standard.